

# 石家庄创泓科技有限公司

SHIJIAZHUANG CHUANGHONG TECHNOLOGY CO., LTD

Catalyst

## HHCP-T-9

### General Description

Stannous Octoate (T-9) is standard stannous tin urethane catalyst for continuous flexible slabstock polyurethane foam applications.

### Applications

T-9 is widely used in the production of flexible slabstock polyether foams. It is also used successfully as a catalyst for polyurethane coatings and sealants.

### Typical Physical Properties

Appearance	Light yellow liquid
Tin content%	28-29
Stannous content%	27.1 - 29.0
Color/Gardner	≤4
Viscosity (mPa.s 25℃)	270.0 - 430.0
Refractive Index (20C)	1.4900 - 1.5000
Chloride Ions content (%)	0.00 - 0.10
Ratio stan. Tin/Total Tin Purity (%)	97.0 - 100.0
Density (20℃)	1.2500 - 1.2700
Flash point℃	142

### Storage and package Information

HeHui Chemical recommends that our catalysts be stored in a dry and cool area under appropriate ventilation conditions. Each container should be closed tightly to avoid contamination with moisture or other negative influences, which could change the products' performance in the end use. The optimum storage temperature is between 10°C and 30°C. Lower and higher storage temperatures are not preferable and should be avoided.

Package: 25 kg/pail , 200 kg/drum or depend on client's requests